



The Pumps with Nine Lives



Model: [2511](#) 25 FRAME PLUNGER PUMP

Specs

Max Flow:	20 gpm
Min Pressure:	100 psi
Max Pressure:	1500 psi
Inlet Port Size:	1.25
Discharge Port Size:	0.75
RPM:	1450
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of 316SS manifold, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle, high pressure systems, and pumping special liquids such as DI water and salt water

Datasheet: [2510-2511 Data Sheet](#)

Service Manual: [15-25 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7022.100](#)

SS Pressure Regulator

Relief / Pop-Off Valve



[9941](#)

Pop-Off Valve



[7034](#)

SS Pressure Relief Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6014](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube

Inlet Filter



[7107.7](#)

Inlet Filter

Flexible Inlet Hose



[990847](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990853](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit