



**Model: [5CP3120CSS](#)
5CP PLUNGER PUMP**

Specs

Max Flow:	4.5 gpm
Min Pressure:	100 psi
Max Pressure:	3500 psi
Inlet Port Size:	.5
Discharge Port Size:	.37
RPM:	1645
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a forged brass manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings Includes side bubble gauge.

Datasheet: [5CP3120-3120CSS-3120CSSG1 Data Sheet](#)

Service Manual: [CP Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7014](#)

Pressure Regulator

Unloader



[7850](#)

Modular Pressure Unloader

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6089](#)

Pressure Gauge

Pulsation Dampener



[6011](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube


Inlet Filter



[7104](#)

Inlet Filter


Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990857](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit