

Thread Tape & Sealant.....M-2 to M-3

PTFE tape	M-2
American made (Purple).....	M-2
Industrial (White).....	M-2
Stainless steel (Gray).....	M-2
Industrial heavy duty (Pink).....	M-2
For LP gas (Yellow)	M-2
Thread sealant paste.....	M-3
Joint sealant gasket material.....	M-3
Leak detector.....	M-3

Coupling Inserters M-4

Coupling inserter for large hose	M-4
Coupling inserter for 5 ton ram	M-4

Testing Equipment.....M-5 to M-7

Hand hydrotest pump	M-5
Hydrostatic test pumps.....	M-6
Hydrostatic test pump accessories.....	M-6
Sprinkler system gauges (UM-393).....	M-7
Line test gauges	M-7
Three way gauge valve	M-7
PITOT gauge	M-7
Sprinkler line tester.....	M-7

AccessoriesM-8 to M-11

Dixon® coupling lubricant	M-8
WD-40 smart straw	M-8
Spill kits	M-8
Dixon® soft hose mallet	M-9
Dixon® hose knife	M-9
Diameter tape	M-9
Screw pitch gauge	M-9
Safety tag	M-10
Safety tape	M-10
Stretch straps	M-11
Pick head fire axe	M-11

Grease Whip FittingsM-12 to M-13

Grease whip hose assemblies.....	M-12
Grease whip hose fittings.....	M-12
Grease whip fittings - Zerk.....	M-13

Oxy-Acetylene Fittings M-14

Oxy-acetylene hose couplings.....	M-14
Oxy-acetylene connecting spuds.....	M-14
Oxy-acetylene adapters.....	M-14
Oxy-acetylene ferrules.....	M-14


WrenchesM-15 to M-16

Micrometer adjustable torque wrenches.....	M-15
C series.....	M-15
Heavy duty industrial.....	M-15
Electronic torque wrench	M-15
Torque and angle meter pro	M-16
Torque and angle meters.....	M-16
Torque meters.....	M-16



American Made PTFE Tape (Purple)

Features:

- thickness: 3.5 mil (0.0035 mm)
- temperature range: **-450°F to 500°F (-268°C to 260°C)**
- superior quality
- not for use in oxygen applications 



Size	Length	Part #	Price/E
1/2"	520"	<i>TTPM50-520</i>	\$5.20
	700"	<i>TTPM50-700</i>	5.80
	1429"	<i>TTPM50-1429</i>	10.30
3/4"	520"	<i>TTPM75-520</i>	7.00
	700"	<i>TTPM75-700</i>	7.60
	1429"	<i>TTPM75-1429</i>	13.70
1"	520"	<i>TTPM100-520</i>	8.50
	700"	<i>TTPM100-700</i>	9.70
	1429"	<i>TTPM100-1429</i>	17.60

Industrial PTFE Tape (White)

Features:

- thickness: 3.5 mil (0.0035 mm)
- temperature range: **-212°F to 500°F (-136°C to 260C)**



Size	Length	Part #	Price/E	Optional Qty
1/2"	260"	<i>TTA50</i>	\$0.90	500
	520"	<i>TTB50</i>	1.75	500
	1296"	<i>TTC50</i>	4.50	500
3/4"	260"	<i>TTA75</i>	1.45	350
	520"	<i>TTB75</i>	2.70	350
1"	520"	<i>TTB100</i>	2.85	250

Stainless Steel PTFE Tape (Gray)

Features:

- thickness: 4 mil
- temperature range: **-450°F to 550°F (-268°C to 288°C)**
- useful on stainless steel threaded joints or connections
- PTFE with nickel added, nickel acts like a ball bearing
- made in the US



Size	Length	Part #	Price/E	Optional Qty
1/2"	260"	<i>TTA50SS</i>	\$15.70	10

Industrial Heavy Duty PTFE Tape (Pink)

Features:

- thickness: 4 mil
- temperature range: **-400°F to 500°F (-240°C to 260°C)**



Size	Length	Part #	Price/E	Optional Qty
1/2"	540"	<i>TTBP50</i>	\$7.50	500



PTFE Tape for LP Gas (Yellow)

Features:

- thickness: 4 mil
- maximum temperature: **500°F (260°C)**
- Underwriters Listed



Size	Length	Part #	Price/E	Optional Qty
1/2"	260"	<i>TTA50LP</i>	\$4.95	500

Thread Sealant Paste

Features:

- temperature range: **-300°F to 500°F (-184°C to 260°C)**
- do not use with oxygen

Size	Part #	Price/E	Optional Qty
¼ pint	LCTS14	\$14.75	24
½ pint	LCTS1	21.55	24
1 pint	LCTS2	33.75	12
1 quart	LCTS3	60.35	12

Maintenance
& Repair

Joint Sealant Gasket Material

Features:

- GORE-TEX® interchangeable
- Form-In-Place expanded PTFE gasket material with adhesive backing
- manufactured from 100% virgin PTFE
- unaffected by all common chemicals (pH from 0-14)
- unlimited shelf life
- resilient with low cold flow
- requires less force than standard gasket materials
- pressure range: **vacuum to 3000 PSI**
- temperature range: **-450°F to 600°F (-268°C to 316°C)**
- made in the USA
- FDA compliant #21CFR177.1550
- larger spools are available, consult Dixon® for price and availability

Size	Length	Part #	Price/E
¼"	20'	LCJS4-20	\$69.45
¼"	50'	LCJS4-50	159.55
⅜"	25'	LCJS6-25	127.50
½"	15'	LCJS8-15	127.50
¾"	15'	LCJS12-15	291.85



Leak Detector

Features:

- detects leaks by forming bubbles which remain for up to ten minutes
- will not cause corrosion or deterioration
- color: fluorescent yellow
- non-toxic, non-freezing
- temperature range: **-7°F to 180°F (-20°C to 82°C)**
- meets Federal specification MIL-L-25567-C

Size	Part #	Price/E	Case Qty
8 oz.	LCLD	\$11.90	24



Coupling Inserter for Large Hose

Features:

- inserts 4", 5", 6", 8", 10" and 12" couplings
- includes CI96AH pump (shown below)
- portable
- coupling inserter pusher plates (not shown) must be purchased separately



Part #	Price/E
CI9	\$5820.00

Hose ID	Part #	Price/E
4" - 5"	45CIPUSH	\$300.00
6" - 8"	68CIPUSH	380.00
10" - 12"	1012CIPUSH	530.25

Coupling Inserters



CI96

Application:

- for insertion of hose shanks into hose with a 2¾" to 7¼" OD



CI96AH

Description	Part #	Price/E
inserter with 10,000 PSI hand pump and 5 ton ram	CI96	\$6580.00
inserter with 10,000 PSI air/hydraulic pump and 5 ton ram	CI96AH	7850.00
small jaws for 1" to 3" OD hose	CI9311SML	189.00



Hand Hydrotest Pump

Applications:

- designed for use in testing pipe lines, pressure tanks and pressure vessels

Features:

- uses check valves which are more efficient and longer lasting than poppet systems
- cylinder displacement: 1.37 cu. in.
- **0 -1000 PSI** pressure gauge, 10' high pressure hose and quick disconnect coupler included
- piston: 7/8" with 2" stroke
- stainless steel piston
- working pressure: **1000 PSI at 70°F (21°C)**

NPT Inlet	NPT Outlet	Aluminum		Price/E
		Part #	Part #	
1/2"	1/2"	HHTP		\$1805.75



Maintenance & Repair

Hydrostatic Test Pumps

Electric Test Pump

Features:

- 1.3 GPM hose fill rate (.28 GPM @ 2000 PSI)
- test pressure: **200 to 2000 PSI**
- suction strainer keeps dirt out of pump
- high pressure test gauge
- 115v motor
- 2' power cord
- easy to use, portable

Part #	Price/E
ETP	\$4600.00



Pneumatic Test Pump

Features:

- 5.5 GPM fill rate
- test pressure: **0 to 1500 PSI**
- stainless interior
- air gauge for quick, easy adjustment of maximum test pressure
- high pressure test gauge
- filter/regulator for clean, dry air to ensure long life of unit
- on - off valve for air input
- 15' of hose included
- easy to use, portable
- use of coalescing filter and water filter recommended for prolonged pump life

Part #	Price/E
PTP	\$6450.00



Hydrostatic Test Pump Accessories

Features:

- cost effective, pre-assembled caps or plugs allow quick set up for testing hoses
- caps and plugs equipped with ½" brass straight-through plug for quick attachment to the intermediate hose on the test pump (Pneumatic Test Pump) and bleed-off valve

cam & groove test caps for male adapters

Size	Iron / Steel		Price/E
	Part #		
1"	ID100TC		\$236.65
1½"	ID150TC		375.15
2"	ID200TC		196.50
3"	ID300TC		350.00
4"	ID400TC		536.00

**cam & groove test plugs for female couplers**

Size	Iron / Steel		Price/E
	Part #		
1"	IA100TP		\$150.00
1½"	IA150TP		175.00
2"	IA200TP		175.00
3"	IA300TP		380.00
4"	IA400TP		410.00

**female NPT test caps**

Size	Iron / Steel		Price/E
	Part #		
1"	NPT100TC		\$135.00
1½"	NPT150TC		170.00
2"	NPT200TC		200.00
3"	NPT300TC		350.00
4"	NPT400TC		410.00

**male NPT test plugs**

Size	Iron / Steel		Price/E
	Part #		
1"	100TP		\$220.00
1½"	150TP		250.00
2"	200TP		240.00
3"	300TP		300.25
4"	400TP		405.00

**bleed-off valve**

Part #	Price/E
IBV50BOV	\$89.80

**FRL Attachment Accessories**

Description	Part #	Price/E
⅜" Wilkerson modular coalescing filter (automatic drain)	M16-03A	\$305.35
⅜" Wilkerson modular coalescing filter (manual drain)	M16-03M	245.00
modular sleeve needed to connect M16-03A or M16-03M	GPA-95-292	17.55

Sprinkler System Gauge (UL-393)



Features:

- specifically designed for the fire sprinkler industry
- Bourdon tube pressure gauges with black polycarbonate case
- snap-in clear polycarbonate window, 4" face
- white aluminum dial with stop pin, black and red markings
- black aluminum non-adjustable pointer
- ¼" NPT lower mount
- ASME B40.1 Grade B (+ 3/2/3% accuracy)
- U/L Listed (U/L-393) and Factory Mutual Approved for fire sprinkler service
- temperature range: **-40°F to 140°F (-40°C to 60°C)**



Maintenance & Repair

Type	Part #	Price/E
water (0-300 PSI)	SWG300-4	\$38.40

Line Test Gauges

Features:

- rocker lug swivel
- used for testing static or flowing pressures in hoses or nozzles
- supplied with **0-300 PSI** glycerine filled 3½" diameter gauge
- freeze proof to **-40°F (-40°C)**
- other sizes and threads are also available, contact Dixon®



NST (NH) Thread	Hardcoated Aluminum	
	Part #	Price/E
1½"	ALTG150F	\$446.30
2½"	ALTG250F	330.00

Three Way Gauge Valve

Features:

- permits checking or replacing a gauge without shutting down the whole line
- disc: rubber



NPT Thread	Working Pressure (PSI)	Brass	
		Part #	Price/E
¼"	175	TWGV25	\$22.10

PITOT Gauge

Features:

- liquid filled gauge 0-160 PSI is standard, other pressures available, contact Dixon®
- supplied with handle grip, case and fire stream/friction loss data



Part #	Price/E
PG8083	\$536.80

Sprinkler Line Tester



Feature:

- installs on the last sprinkler head on system branch lines and controls water flow for flushing or testing the system



Inlet	Outlet	Brass	
		Part #	Price/E
1" female NPT	1" male NPSH	SLT10050	\$112.75

Dixon® Coupling Lubricant



Application:

- For use in assembly operations involving natural or synthetic rubber or plastic. Also an excellent lubricant when rubber or plastic needs to be cut, machined, pressed, turned, trimmed or ground.

Features:

- biodegradable lubricant for coupling shanks, O-rings, hoses, sleeves, rubber washers and grommets
- once coupling lubricant dries, slipping action goes away

Size	Part #	Price/E
1 liter	DCL20	\$36.50
4 liters	DCL80	94.50

WD-40 Smart Straw



Features:

- permanently attached straw
- flip up for a precision spray; flip down for regular spray action
- sold in case quantities only
- should not be used as a lubricant for coupling shanks



Size	Part #	Price/E	Case Qty
11 oz.	WD40	\$21.00	12

Spill Kits



oil spill kit



universal spill kit

Features:

- easily stored behind a seat or in a storage compartment allowing drivers to act quickly when responding to a spill
- poly-zip bag and bucket kits feature:
 - 10 pads (15" x 19")
 - 3 socks (3" x 4')
 - 2 disposal bags with ties
 - 1 pair nitrile gloves

Description	Part #	Price/E
oil only, in 6½ gallon pail	DSK5-O	\$122.10
universal, in 6½ gallon pail	DSK5-U	118.40
oil only, in clear poly bag with zipper	DSKB-O	85.10
universal, in clear poly bag with zipper	DSKB-U	80.15



Dixon® Soft Hose Mallet

Features:

- soft mallet for pounding metal objects without damaging them
- The head material will not crack and is firmly attached to strong shaft-handle.
- length: 23"
- weight: 10 lbs.



Maintenance & Repair

Part #	Price/E
DCM1	\$375.00

Dixon® Hose Knife

Features:

- for fast cutting of rubber hose and belting
- guard protects hand while cutting



Part #	Price/E
DRK15	\$24.35

Diameter Tape

Features:

- 6' tape for quickly finding the outside diameter of any cylindrical object
- converts circumference to OD at the measured point
- ABS case



Part #	Price/E
DDT1	\$18.25

Screw Pitch Gauge

Features:

- used to determine threads per inch
- 30 leaves



Part #	<i>Stainless Steel</i>	Price/E
TPG		\$224.25



Safety Tag

**Features:**

- Dixon® strongly recommends the use of a safety tag or warning label on all hose assemblies.
- sold in quantities of 100 only



Length	Width	Part #	Price/E
5"	2 $\frac{3}{8}$ "	DWL100	\$0.40

**WARNING!!**

- worn-out hose fittings should be replaced
- loose clamps on hose can be dangerous
- bolt type clamps should be retensioned regularly
- for extra safety, retaining devices such as clips, chains or cables must be used

Safety Tape

Features:

- Dixon® strongly recommends the use of a safety tag or warning label on all hose assemblies.
- length of tape - 55 yards, approximately 255 warnings



Length	Part #	Price/E
1 $\frac{1}{2}$ "	DSTW	\$22.00

**WARNING!!**

- worn-out hose fittings should be replaced
- loose clamps on hose can be dangerous
- bolt type clamps should be retensioned regularly
- for extra safety, retaining devices such as clips, chains or cables must be used

Stretch Straps

Features:

- durable tie down straps
- made of EPDM
- length does not include S-hooks
- S-hooks are steel

Length	Part #	Price/E
10"	SSE10	\$3.00
15"	SSE15	3.80
21"	SSE21	4.40
31"	SSE31	5.20
41"	SSE41	6.25



WARNING!!

Failure to comply with this warning may result in serious damage and/or personal injury.

Maximum end to end safe stretch = 150% of length

- do not exceed maximum safe stretch
- inspect before each use, do not use if strap is cut, cracked or abraded
- inspect hooks for damage and/or wear. Replace if needed.
- protect strap from sharp edges or heat.
- wear eye protection during use
- do not use this product as the primary tie down
- refer to federal or state regulations for proper tie down methods



Maintenance
& Repair

Pick Head Fire Axe

Features:

- red trim
- 36" hickory handle
- listed in the minimum requirements approval guides for outfitting hose houses and hose cabinets by insurance underwriters

Description	Part #	Price/E
6 lb. axe	PHFA6	\$220.00
axe brackets	PHFA-B-A	59.10



Grease Whip Hose Assemblies

Features:

- for use with hand grease guns only
- one piece crimp couplings
- 1/8"-27 male NPT thread, solid base
- US manufactured 3/16" ID hose - exceeds SAE 100R1-AT
- add "S" to order strain relief spring option
- working pressure: **3000 PSI**



Assembly Length	Previous Part #	Brass		Price/E
		Part #	Price/E	Strain Relief Spring Option
8"	GWH-0800	GWH0800	\$12.63	\$20.68
12"	GWH-1200	GWH1200	14.66	20.05
	---	GWH1200R¹	19.40	---
18"	GWH-1800	GWH1800	17.91	23.32
	---	GWH1800R¹	23.08	---
24"	GWH-2400	GWH2400	21.55	26.46
36"	GWH-3600	GWH3600	28.80	35.44
48"	GWH-4800	GWH4800	39.46	48.65
60"	GWH-6000	GWH6000	44.81	63.83

¹ retail packaging

Grease Whip Hose Fittings

Features:

- **001-0055**, **001-0260** and **001-0860** are designed to be crimped to 3/16" ID hose
- **GWH-C** and **GWHC-FF** mate with Zerk fittings on the coupler side

grease hose couplers



Description	Zinc Plated Steel				Optional Qty
	Previous Part #	Part	Price/E	Price/Retail Pk	
1/8"-27 female NPT thread, grease hose coupler with ball check - valved shutoff	GWH-C	GWHC	\$8.15	\$10.31	25
1/8"-27 female NPT thread, full flow grease hose coupler	---	GWHC-FF	8.15	10.31	25

Add 'R' suffix to part number for retail pack option

male NPT thread - chamfered base



Description	Brass			Optional Qty
	Previous Part #	Part #	Price/E	
1/8"-27 male NPT thread, drilled and chamfered base	001-0055	0010055C	\$3.30	100

male NPT thread - solid base



Description	Brass			Optional Qty
	Previous Part #	Part #	Price/E	
1/8"-27 male NPT thread, solid base	001-0260	0010260C	\$2.70	100

female NPT thread



Description	Brass			Optional Qty
	Previous Part #	Part #	Price/E	
1/8"-27 female NPT thread	001-0860	0010860C	\$6.16	100

Grease Whip Fittings - Zerk

straight

Thread	Description	Overall Length	Thread Length	Hex	Zinc Plated Steel		Pkg Qty
					Part #	Price/E	
1/8"-27 NPT	straight	.660"	.260"	.430	GWHZ000	\$0.81	100
1/4"-28 tapered SAE-LT	straight	.530"	.200"	.312	GWHZ400	0.63	100

Maintenance
& Repair

45°

Thread	Description	Overall Length	Thread Length	Hex	Zinc Plated Steel		Pkg Qty
					Part #	Price/E	
1/8"-27 NPT	45°	.860"	.280"	.430	GWHZ045	\$1.11	100
1/4"-28 tapered SAE-LT	45°	.800"	.200"	.375	GWHZ445	1.13	100



90°

Thread	Description	Overall Length	Thread Length	Hex	Zinc Plated Steel		Pkg Qty
					Part #	Price/E	
1/8"-27 NPT	90°	.830"	.310"	.430	GWHZ090	\$1.12	100
1/4"-28 tapered SAE-LT	90°	1.20"	.200"	.375	GWHZ490	1.13	100



Grease Whip Fittings - Zerk Retail Packaged

All items sold in retail packets of 10: Order 1 for 1 Retail Pack of 10 pieces.

straight

Thread	Description	Overall Length	Thread Length	Hex	Zinc Plated Steel	
					Part #	Price/ Retail Pk
1/8"-27 NPT	straight	.660"	.260"	.430	GWHZ000R	\$10.54
1/4"-28 tapered SAE-LT	straight	.530"	.200"	.312	GWHZ400R	8.72



45°

Thread	Description	Overall Length	Thread Length	Hex	Zinc Plated Steel	
					Part #	Price/ Retail Pk
1/8"-27 NPT	45°	.860"	.280"	.430	GWHZ045R	\$13.36
1/4"-28 tapered SAE-LT	45°	.800"	.200"	.375	GWHZ445R	13.52



90°

Thread	Description	Overall Length	Thread Length	Hex	Zinc Plated Steel	
					Part #	Price/ Retail Pk
1/8"-27 NPT	90°	.830"	.310"	.430	GWHZ090R	\$13.44
1/4"-28 tapered SAE-LT	90°	1.20"	.200"	.375	GWHZ490R	13.52



Oxy-Acetylene Hose Couplings

acetylene couplings

left-hand thread for acetylene line x hose shank



Hose Size	Left UNF Thread	Hex	Previous Part #	Brass	
				Part #	Price/E
3/16"	3/8"-24	7/16"	OA69	1540306K	\$5.93
	9/16"-18	11/16"	OA70	1540309K	4.15
1/4"	9/16"-18	11/16"	OA71	1540409K	3.61
5/16"	9/16"-18	11/16"	OA72	1540509K	4.60
3/8"	9/16"-18	11/16"	OA73	1540609K	4.32

oxygen couplings

right-hand thread for oxygen line x hose shank



Hose Size	Right UNF Thread	Hex	Previous Part #	Brass	
				Part #	Price/E
3/16"	3/8"-24	7/16"	OA59	1520306K	\$5.93
	9/16"-18	11/16"	OA60	1520309K	4.24
1/4"	9/16"-18	11/16"	OA61	1520409K	3.63
5/16"	9/16"-18	11/16"	OA62	1520509K	4.78
3/8"	9/16"-18	11/16"	OA63	1520609K	4.20

Oxy-Acetylene Connecting Spuds

left-hand thread x left-hand thread



Left UNF Thread	Hex	Previous Part #	Brass	
			Part #	Price/E
9/16"-18	11/16"	OA52	1580909C	\$4.53

right-hand thread x right-hand thread



Right UNF Thread	Hex	Previous Part #	Brass	
			Part #	Price/E
9/16"-18	11/16"	OA50	1560909C	\$4.28

Oxy-Acetylene Adapters

left-hand thread x NPTF



Left UNF Thread	NPTF Thread	Hex	Previous Part #	Brass	
				Part #	Price/E
9/16"-18	1/4"	5/8"	158-0904	1580904C	\$3.45
	3/8"	11/16"	158-0906	1580906C	4.67

right-hand thread x NPTF



Right UNF Thread	NPTF Thread	Hex	Previous Part #	Brass	
				Part #	Price/E
9/16"-18	1/4"	5/8"	156-0904	1560904C	\$3.42
	3/8"	11/16"	156-0906	1560906C	4.28

Oxy-Acetylene Ferrules

• sold in package quantities only



Inside Dimensions	Overall Length	Metal Gauge	Standard Ind. Part #	Brass		Qty
				Part #	Price/E	
.458" x 0.890"	15/32"	.019"	9116	BFO448	\$0.71	25
.474" x 0.943"	15/32"	.019"	9979	BFO474	0.52	25
.535" x 1.071"	3/4"	.024"	9940P	BFO535	0.85	25
.593" x 1.109"	3/4"	.024"	9593	BFO593	0.78	25
.700" x 1.325"	.719"	.025"	8337	BFO700	3.65	25

Micrometer Adjustable C Series Torque Wrenches

Features:

- 36 tooth quick release ratchet head
- certification readings and individual instrument serial number are included
- certified to meet the accuracy specified in ANSI B107.14M-1994, calibrated on a torque standard that is traceable to the National Institute of Standards Technology (NIST)
- accurate to $\pm 3\%$ and $\pm 5\%$ CCW of full scale

Drive	Range		Length	Plated Steel	
	In-Lb	Ft-Lb		Part #	Price/E
1/4"	20 - 100	---	11"	C1001	\$360.00
	40 - 200	---	16"	C2001	360.00
3/8"	---	15 - 100	17"	C1002	390.00
1/2"	---	20 - 150	24"	C1503	400.00
	---	30 - 250	24"	C2503	420.00



Maintenance
& Repair

Micrometer Adjustable Heavy Duty Industrial Torque Wrenches

Features:

- 24 tooth quick release ratchet head
- click type wrench
- equipped with 3/4" or 1" dual direction quick release, 24 tooth ratchet
- precision roll marked scale
- polished durable bright chrome finish
- fully repairable and easily calibrated
- calibrated to $\pm 3\%$ at any setting
- meets ASME B107.14B

Drive	Range Ft-Lb	Length	Plated Steel	
			Part #	Price/E
3/4"	50 - 450	41.9"	C4504	\$1100.00
	100 - 600	49.8"	C6004	1250.00
	150 - 750	49.8"	C7504	1400.00
1"	100 - 600	49.8"	C6005	1320.00
	150 - 750	49.8"	C7505	1600.00



Electronic Torque Wrenches

Features:

- 24 tooth quick release ratchet head
- 5 alphanumeric digit display, 4 keys: up, down, mode, unit
- 3 colored lights, vibration and audible alarm
- unit: ft-lb, in-lb and Nm.
- mode: Peak Hold
- torque setting from 5% to 100% of full scale
- accuracy torque $\pm 1\%$ both CW and CCW from 10%-100% of Indicate value
- 2 AA batteries provide up to 500 hours of continuous use
- ISO-6789-2003 and ASME B107-2005 Standard compliant
- Certificate of N.I.S.T. traceability for 10% to 100% of full scale

Drive	Range		Length	Part #	Price/E
	In-Lb	Ft-Lb			
1/4"	12.5 - 250	1 - 20.7	13"	DW2501	\$590.00
3/8"	60 - 1200	5 - 100	18"	DW1002	590.00
1/2"	150 - 3000	12.5 - 250	26.5"	DW2503	720.00



Torque and Angle Meter Pro

Features:

- 5 alphanumeric digit display, 4 keys: up, down, mode, unit
- 3 colored lights, vibration and audible alarm
- unit: ft-lb, in-lb and nM
- mode: Track, Peak Hold and Angle
- torque setting from 5% to 100% of full scale
- accuracy torque $\pm 1\%$ both CW and CCW from 10% - 100% of Indicate value
- accuracy angle: $\pm 1^\circ$ of reading $\pm 1^\circ$ from 1° to 360°
- angle setting: 5° to 360° , angular velocity $>4^\circ/\text{sec}$ and $<200^\circ/\text{sec}$
- Li-Ion rechargeable battery provides up to 200 hours use per charge
- ISO-6789-2003 and ASME B107-28-2005 Standard compliant
- Certificate of N.I.S.T. traceability for 10% to 100% of full scale



Drive	Range		Length x Width	Part #	Price/E
	In-Lb	Ft-Lb			
3/8"	30 - 600	2.5 - 50	3.5" x 2.1"	SPA502	\$630.00
	60 - 1200	5 - 100	3.5" x 2.1"	SPA1002	640.00
1/2"	90 - 1800	7.5 - 150	3.75" x 2.1"	SPA1503	650.00
	150 - 3000	12.5 - 250	3.75" x 2.1"	SPA2503	670.00
3/4"	240 - 4800	20 - 400	4.5" x 2"	SPA4004	830.00
	360 - 7200	30 - 600	4.5" x 2"	SPA6004	1100.00

Torque and Angle Meters

Features:

- 4 alphanumeric digit display, 4 keys: up, down, mode, unit
- 3 colored lights, vibration and audible alarm
- unit: ft-lb, in-lb and nM
- mode: Peak Hold and Angle
- torque setting from 5% to 100% of full scale
- accuracy torque $\pm 2\%$ both CW and CCW from 10% - 100% of Indicate value
- accuracy angle: $\pm 1^\circ$ of reading from 1° to 180°
- angle setting: 5° to 180° , angular velocity $>10^\circ/\text{sec}$ and $<200^\circ/\text{sec}$
- 3 AAA battery provides up to 200 hours of continuous use
- ISO-6789-2003 and ASME B107-28-2005 Standard compliant
- Certificate of N.I.S.T. traceability for 10% to 100% of full scale



Drive	Range		Length x Width	Part #	Price/E
	In-Lb	Ft-Lb			
3/8"	30 - 600	2.5 - 50	3.5" x 2.1"	TA502	\$470.00
	60 - 1200	5 - 100	3.5" x 2.1"	TA1002	470.00
1/2"	90 - 1800	7.5 - 150	3.75" x 2.1"	TA1503	530.00
	150 - 3000	12.5 - 250	3.75" x 2.1"	TA2503	530.00

Torque Meters

Features:

- 4 alphanumeric digit display, 4 keys: up, down, mode, unit
- 3 colored lights, vibration and audible alarm
- unit: ft-lb, in-lb and nM
- mode: Peak Hold and Angle
- torque setting from 5% to 100% of full scale
- accuracy torque $\pm 2\%$ both CW and CCW from 10% - 100% of Indicate value
- 3 AAA battery provides up to 400 hours of use per charge
- ISO-6789-2003 and ASME B107-28-2005 Standard compliant
- Certificate of N.I.S.T. traceability for 10% to 100% of full scale



Drive	Range		Length x Width	Part #	Price/E
	In-Lb	Ft-Lb			
3/8"	30 - 600	2.5 - 50	3.5" x 2.1"	TM502	\$375.00
	60 - 1200	5 - 100	3.5" x 2.1"	TM1002	375.00
1/2"	90 - 1800	7.5 - 150	3.75" x 2.1"	TM1503	430.00
	150 - 3000	12.5 - 250	3.75" x 2.1"	TM2503	430.00