



NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

HD-Mill™

EPDM Rubber Lining / Polyester Single Jacket

HD-MILL™ DISCHARGE HOSE FEATURES

- **Poly-Cord™** ring spun polyester warp yarns are combined with filament polyester filler yarns.
- The EPDM rubber lining is unaffected by Ozone deterioration.
- The **Dura-Bond™** vulcanized adhesion system, which creates both a mechanical and chemical bond between the EPDM lining and the jacket, reduces the probability of delamination as is experienced with competitive adhesive bonded rubber lined constructions.
- Immune to the effects of mildew and rot, requiring less maintenance after use.
- The hose is made and assembled in the USA, available with either imported or domestic couplings in aluminum or brass.



 **FAMILY OWNED
AMERICAN MADE**

Available in 50, 75 and 100 foot lengths

* 250 PSI acceptance test pressure rating-not rated for service test/acceptance/burst test pressure requirements of NFPA 1961.

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
1"	HD-MILL	250 PSI	NA	1 ¼"	8 lbs.
1 ½"	HD-MILL	250 PSI	NA	1 ¾"	10.5 lbs.
2"	HD-MILL	250 PSI	NA	2 ¼"	13 lbs.
2 ½"	HD-MILL	250 PSI	NA	2 ¾"	18.5 lbs.
3"	HD-MILL	250 PSI	NA	3 ¼"	23 lbs.
4"	HD-MILL	250 PSI	NA	4 ¾"	25 lbs.

HD-Mill,™ Poly-Cord,™ and Dura-Bond™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

