

Hi-Flow 400 LDH[™]

Nitrile Rubber / Through-The-Weave Construction

HIGH FLOW 400 LDH™ FEATURES

- 100% synthetic reinforcement, totally encapsulated in a nitrile rubber compound utilizing a through-the-weave process.
- A heavy duty rubber hose construction with good heat and chemical resistance.
- Both the hose and couplings are made in the USA, performance shall meet and exceed NFPA 1961 standards.
- · Available in yellow and red.

Applications: Supply and LDH

Available in 25, 50 and 100 foot lengths





HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 100' UNCPLD
4"	HF-400	400 PSI	200 PSI	45/16"	80 lbs.
5"	HF-400	400 PSI	200 PSI	55/16"	110 lbs.

 $HF\text{-}400, ^{\intercal}\text{M} \text{ and Hi-Flow } 400 \, LDH, ^{\intercal}\text{M} \text{ are trademarks of North American Fire Hose Corporation. All rights reserved.}$

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454 Tel: 805.922.7076 • Fax: 805.922.0086 NAFHC.com