



# NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

## IA-600 Lite™

EPDM Rubber Lining / Polyester Double Jacket

### INDUSTRIAL ATTACK-600 LITE™ FEATURES

- **Poly-Cord™** ring spun polyester warp yarns are combined with filament polyester filler yarns.
- Available either plain / uncoated “natural” white, or with our optional **Ultra-Shield™** high-performance polyurethane coating applied to seal each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The EPDM rubber lining is unaffected by Ozone deterioration, and is one component in the **Friction Fighter System™**, creating an extremely smooth waterway surface, thereby reducing friction loss and improving nozzle performance.
- The **Dura-Bond™** vulcanized adhesion system, which creates both a mechanical and chemical bond between the EPDM lining and the jacket, reduces the probability of delamination as is experienced with competitive adhesive bonded rubber lined constructions.
- The result is a very strong, flexible, and “Tuff” hose, with good heat and chemical resistance.
- The hose is made and assembled in the USA, available with either imported or domestic couplings in aluminum or brass. Performance shall meet and exceed NFPA 1961 Standards.

Available in 50, 75 and 100 foot lengths



 **FAMILY OWNED  
AMERICAN MADE**

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
1½"	IA-600	600 PSI	300 PSI	1 15/16"	15 lbs.
2½"	IA-600	600 PSI	300 PSI	3"	27 lbs.
3"	IA-600	600 PSI	300 PSI	3 17/32"	34 lbs.

Industrial Attack-600 Lite,™ IA-600 Lite,™ Poly-Cord,™ Ultra-Shield,™ Friction Fighter System™ and Dura-Bond™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

### NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

