


Outback 600™

Polyurethane (TPU) Lining / Polyester Single Jacket

Outback 600™ FEATURES

- Poly-Cord[™] ring-spun polyester warp yarns are combined with filament polyester filler yarns.
- Fabric construction features a very fine twill weave for improved abrasion and snagging resistance in wildland fire fighting situations.
- High visibility yellow *Ultra-Shield™* polymeric coating seals each and every fiber in the bundle, further improving abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The *Dura-Thane*[™] polyurethane inner lining is extremely strong and durable, while maintaining a lightweight and compact profile.



- Designed to withstand the rigors of the Outback, as well as other wildland fire fighting situations.
- Both the hose and couplings are made in the USA, performance shall meet and exceed NFPA 1961 standards.

Applications:Forestry, Wildland and CAFS Available in 50, 75 and 100 foot lengths





HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 100' UNCPLD
1"	OB-600	600 PSI	300 PSI	11⁄4"	10 lbs.
11/2"	OB-600	600 PSI	300 PSI	1¾"	14 lbs.

OB-600,™ Outback 600,™ Ultra-Shield,™ Poly-Cord™ and Dura-Thane™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454 Tel: 805.922.7076 • Fax: 805.922.0086 NAFHC.com