


Novaflex 3253 Tank Truck Hose



Nitrile tube designed for use with oil, gasoline and other petroleum products. Ideal for pressure, gravity flow or suction service from tank trucks, tank cars or bulk plants. Steel wire helix is spiraled between multiple plies of tire cord to reinforce hose to resist crushing and kinking. Black neoprene cover is abrasion, oil and weather resistant.

Construction:

Tube: Nitrile

Reinforcement: Multiple plies polyester tire cord and steel wire helix


Cover: Black neoprene

Length: 100 ft.

Temperature Range: -30°F to +180°F

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3253-01250-00	1¼	1.73	2	3	30"	150	0.71
3253-01500-00	1½	1.98	2	3	30"	150	0.80
3253-02000-00	2	2.49	2	4	30"	150	1.08
3253-02500-00	2½	3.01	2	5	30"	150	1.44
3253-03000-00	3	3.57	2	6	30"	150	1.90
3253-04000-00	4	4.57	2	8	30"	150	2.49
3253-06000-00	6	6.77	2	30	30"	150	5.31

Novaflex 3260 Tank Truck/Vacuum Hose



A very flexible economical, lightweight designed for transfer of petroleum products. Excellent for use in oil field applications.

Construction:

Tube: Nitrile.

Reinforcement: Multiple plies polyester tire cord and steel wire helix

Cover: Smooth black cover

Length: 100 ft.

Temperature Range: -30°F to +180°F

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3260-01225-00	1¼	1.73	2	3	30"	150	0.71
3260-01500-00	1½	1.95	2	3	30"	150	0.79
3260-02000-00	2	2.45	2	4	30"	150	1.00
3260-02500-00	2½	3.00	2	5	30"	150	1.33
3260-03000-00	3	3.55	2	6	30"	150	1.85
3260-04000-00	4	4.55	2	8	30"	150	2.40

Novaflex 3255 Corrugated Tank Truck Hose



A medium duty petroleum suction and transfer hose designed to be highly flexible with a hose cover that provides extra abrasion resistance to meet the demanding requirements of the industry. Handles all grades of petroleum with aromatic contents to 55%.

Construction:

Tube: Black Nitrile

Reinforcement: Multiple plies tire cord with helix

Cover: Corrugated black oil and abrasion resistant rubber

Length: 100 ft.

Temperature Range: -30°F to +180°F

Novaflex 3256 - 200PSI WP Tank Truck available on request

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3255BT-01250-00	1¼	1.73	2	3	30"	150	0.71
3255BT-01500-00	1 1/2	1.96	2	3	30"	150	0.84
3255BT-02000-00	2	2.46	2	4	30"	150	1.08
3255BT-02500-00	2½	3.01	2	5	30"	150	1.44
3255BT-03000-00	3	3.52	2	6	30"	150	1.85
3255BT-04000-00	4	4.63	2	10	30"	150	3.11
3255BT-06000-00	6	6.72	2	30	30"	150	5.73

Petroleum Hose - Tank Truck



Novaflex 3258 Crush & Kink Resistant Petroleum Suction and Discharge Hose



Special kink and crush resistant version of Novaflex 3253 design, utilizing a multi-ply construction with dual monofilament helix rods. Excellent for use in those demanding abusive situations.

Construction:

Tube: Nitrile resistant to 55% aromatic fuels
Reinforcement: Multiple plies of tire cord with dual monofilament helix
Cover: Black oil and abrasion resistant compound
Length: 100 ft.
Temperature Range: -40°F to +180°F

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3258-01250-00	3/4		2	3	30"	200	0.71
3258-01500-00	1½		2	5	30"	200	0.84
3258-02000-00	2		2	6	30"	200	1.08
3258-02500-00	2½		2	5	30"	200	1.44
3258-03000-00	3		2	10	30"	200	1.85

Novaflex 3257 Corrugated Low Temp Tank Truck



A medium duty low temperature petroleum suction and transfer hose designed to be highly flexible with a hose cover that provides extra abrasion resistance to meet the demanding requirements of industry. Handles all grades of gasoline with aromatic contents to 55%.

Construction:

Tube: Black Nitrile
Reinforcement: Multiple plies polyester tire cord with helix.
Cover: Corrugated red oil resistant rubber
Length: 100 ft.
Temperature Range: -65°F to +180°F

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3257BT-01250-00	1¼	1.73	2	3	30"	150	0.71
3257BT-01500-00	1 1/2	2.00	2	4	30"	150	0.84
3257BT-02000-00	2	2.50	2	4	30"	150	1.08
3257BT-02500-00	2½	3.07	2	6	30"	150	1.44
3257BT-03000-00	3	3.57	2	9	30"	150	1.85
3257BT-04000-00	4	4.67	2	14	30"	150	3.11

Novaflex 3549 Petroleum Discharge Hose



A lightweight petroleum discharge hose. Handles all grades of petroleum with aromatic content to 55%

Construction:

Tube: Black Nitrile
Reinforcement: Multiple plies of tire cord with static wire
Cover: Black oil and abrasion resistant rubber.
Length: 100ft.
Temperature Range: -30°F to +180°F

Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3549BT-02000-00	2	2.39	2	n/a	n/a	200	1.08
3549BT-03000-00	3	3.57	2	n/a	n/a	200	1.85
3549BT-04000-00	4	4.67	2	n/a	n/a	200	3.11