

## PENTEK PCC SERIES HEXAMETAPHOSPHATE CRYSTAL CARTRIDGES

REDUCES SCALE, CORROSION AND IRON IN WATER

---



**Pentair<sup>®</sup> Pentek<sup>®</sup> PCC Series Filter Cartridges contain hexametaphosphate that dissolves slowly in water to inhibit scale and rust build-up.**

**These cartridges are available in four feeder sizes with variable volumes of phosphate crystals.**

**They are effective for treating scale, corrosion and iron problems for up to six months at various flow rates and feed concentrations.**

**The PCC212 and PCC218 Cartridges are designed to fit Pentek #10 Standard or Slim Line Filter Housings. The PCC-1 Cartridge is designed to fit in #10 Standard Filters only.**

**The PCC-106 is an insert element that is placed in the center core of the cartridge. It is designed for use with standard 10" and 20" radial flow, sediment and carbon block double open-ended filter cartridges.**

**This type of treatment is recommended for use with ice machines, coffee and vending machines, food service equipment, water heaters, air conditioning equipment and many other types of water processing equipment.**

### FEATURES/BENEFITS

---

Hexametaphosphate crystals help prevent lime and scale deposits

Effective for treating corrosion and iron problems

Four unique designs to fit multiple applications

Variety of media volumes and flow rates

### SPECIFICATIONS

---

Filter Media – Polyphosphate

Shell – Polypropylene

Post-Filter – Polypropylene

Gaskets – Buna-N  
(PCC212 and PCC218)

Temperature Rating –  
40-100°F (4.4-37.8°C)

## SPECIFICATIONS AND PERFORMANCE

MODEL #	PART #	MAXIMUM DIMENSIONS	INITIAL ΔP (PSI)†‡ FLOW RATE (GPM)
PCC-1	155100-43	2.88" x 9.63" (73 mm x 244 mm)	Up to 5 gpm (19 Lpm)
PCC-106	155632-43	1.06" x 5.44" (27 mm x 138 mm)	1 to 1.5 gpm (4 to 6 Lpm) for insertion in center core of open core cartridges
PCC212	155248-43	2.63" x 9.75" (67 mm x 248 mm)	1 to 1.5 gpm (4 to 6 Lpm)
PCC218	155251-43	2.63" x 9.75" (67 mm x 248 mm)	1.5 to 2.5 gpm (6 to 10 Lpm)

NOTES: Pentek PCC212 and PCC218 Cartridges are not recommended for main line water applications with flow rates exceeding 3.0 gpm (11.4 lpm). With steamers, the water should be flushed daily.

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

CAUTION: Eye irritant. Contains sodium calcium hexametaphosphate. Avoid contact with eyes. In case of eye contact, flush with water for 15 minutes, seek medical attention. Keep out of reach of children.

**Scale:** Hardness particles are kept separated so they cannot precipitate and form deposits when heated; maximum hardness 15 gpg

**Corrosion:** A protective coating is formed on all metal surfaces, safeguarding against acidity/alkalinity, hardness, chloride and other factors which affect the corrosion of water equipment and pipes; pH range 6.5-9.0

**Iron:** Dissolved iron, up to 1 ppm, is kept suspended in solution (sequestered), preventing dissolved iron from precipitating, which would cause staining and discoloration



### WATER QUALITY SYSTEMS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404

WATERPURIFICATION.PENTAIR.COM

CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2015 Pentair Residential Filtration, LLC. All rights reserved.

†For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com](http://waterpurification.pentair.com).

Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

310085 REV E MY15