

# F-Series Filters & Filter Regulators

i035\_0217

Piggyback filters & filter regulators

**Provides CLEAN AIR to your applications at a LOW COST!**



**RT-FR250-G**



**RT-FR500-G**

## Features

- ¼" (RT-FR250-G) or ½" (RT-FR500-G)
- Adjustable 0-120 PSI regulator
- Filter/Regulator with glass face chrome gauge
- Low pressure drop
- Can be wall mounted or panel nut mounted
- Low cost, high efficiency design
- Semi-automatic drain with manual override
- Filters to 5 micron
- Max. pressure: 230 PSI (RT-FR250-G) 180 PSI (RT-FR500-G)
- Temperature range from 40 °F to 120 °F
- 30 scfm (RT-FR250-G) 80 scfm (RT-FR500-G) rating



**RT-F250**



**RT-F500**

## Features

- ¼" (RT-F250) or ½" (RT-F500)
- Low pressure drop
- Can be wall mounted or panel nut mounted
- Low cost, high efficiency design
- Semi-automatic drain with manual override
- Lightweight, high efficiency design is durable and rugged
- Filters to 5 micron
- Max. pressure: 230 PSI (RT-F250) 180 PSI (RT-F500)
- Temperature range from 40 °F to 120 °F
- 30 scfm (RT-F250) 80 scfm (RT-F500) rating



(800) 521-9200



[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)



@RTiPBE



@rti\_pbe

