



## Technical Specifications

**Package Includes:**..... Motor, Pump Tube, Hose, Storage Bracket, Barrel Adapter & Hand Nozzle

**Motor Type:**..... Open Drip Proof (IP44)

**Pump Tube Material:**..... CPVC, PVDF, Hastelloy C-276, Carbon Graphite

**Immersion Length:**..... 39" (1000 mm) or 47" (1200 mm)

**Discharge Hose:** .....PVC, 6 ft (1,8 m), 1" (25 mm) I.D.

**Hand Nozzle Material:** .....Polypropylene, Viton

**Maximum Flow Rate:**..... 15 GPM (57 LPM) *based on water*

**Maximum Viscosity:** ..... 1500 cps (mPas)

**Maximum Temperature:** ..... 175° F (80° C)

**Shipping Weight:**..... 22 lbs. (9,97 kg)

RECOGNIZED COMPONENT



Intertek



## DRUMS

Package P/N	Motor	Volts	Pump Tube
9430	SP-280P-V	110V	SP-CPVC-39
9431	SP-280P-2-V	220V	SP-CPVC-39

## TANKS

Package P/N	Motor	Volts	Pump Tube
9432	SP-280P-V	110V	SP-CPVC-47
9433	SP-280P-2-V	220V	SP-CPVC-47



**Warning:** This pump is not suitable for use with Flammable/Combustible liquids.

\*Note: When pumping viscosities over 1,000 cps, pump must be used intermittently to avoid potential premature failure and/or damage.